## NSN 5935-01-153-2599

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-153-2599

**Body Style:** Rectangular shape **Overall Length:** 2.625 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 2.280 inches **Overall Height:** 1.625 inches **Overall Width:** 1.000 inches **Unthreaded Mounting Hole Diameter:** 0.156 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.468 inches **Mating End Quantity: Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Guide pin/socket and 2 polarization posts **Connector Locking Method:** Friction **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and nickel single mating end single contact grouping **Insert Material:** Glass single mating end and plastic single mating end **Contact Surface Treatment Specification:** Mil-g-45204, type 2 military specification 1st treatment response single mating end single contact grouping and qq-n-290, class 2 federal specification 2nd treatment response single mating end single contact grouping **Terminal Type:** Crimp single mating end single contact grouping **Guide Design And Location:** D shape socket right-hand bottom at 1 oclock **Insert Material Specification:** 

**Included Contact Quantity:** 

60 single mating end single contact grouping

**Included Contact Type:** 

Round socket single mating end single contact grouping

Mil-m-14 military specification all material responses single mating end

## NSN 5935-01-153-2599

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.060 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-g-45204 spec.