Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-154-4533

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
0.594 inches
Cable Entrance Diameter:
0.083 inches
Distance From Mounting Shoulder To Front Face:
0.236 inches
Mounting Facility Thickness:
0.100 inches
Threaded Device Type:
Mounting bushing
Mating End Quantity:
1
Contact Position Arrangement Style:
Nonstd single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Spring friction
Connector Cable Strain Relief Method:
Compression nut
Radio Frequency Type Contact Characteristic Impedance In Ohms:
50.0 single mating end single contact grouping
Thready Qty Per Inch (tpi):
32
Thread Size:
0.190 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and copper single mating end single contact grouping
Insert Material:
Plastic tetrafluoroethylene single mating end



Contact Surface Treatment Specification: Mil-g-45204 military specification 1st treatment response single mating end single contact grouping and mil-c-14550 military specification 2nd treatment response single mating end single contact grouping **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Copper alloy **Shell Surface Treatment:** Gold and copper Shell Surface Treatment Specification: Mil-g-45204 military specification 1st treatment response and mil-c-14550 military specification 2nd treatment response **Included Contact Quantity:** 1 single mating end single contact grouping **Bushing Accommodation Hole Shape:** Round keyed **Included Contact Type:** Coaxial pin single mating end single contact grouping **Precious Material And Weight:** 0.105 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unf Shelf Life: N/a Unit Of Measure: --**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.