

View Online at <https://aerobasegroup.com/nsn/5935-01-154-4646>

Thread Class:

2b

Thread Direction:

Right-hand and right-hand

Body Style:

Straight shape, internal coupling

Overall Length:

36.5 millimeters

Overall Diameter:

43.3 millimeters

Environmental Protection:

Moisture proof and salt water resistant and vibration proof

Threaded Device Type:

Back shell and coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

21-11 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Internally threaded coupling nut

Operating Temperature Rating:

Between 65.0 degrees celsius and 175.0 degrees celsius

Thready Qty Per Inch (tpi):

10

Thread Size:

31.0 millimeters and 1.375 inches

Thread Pitch In Millimeters:

1.00

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416 federal specification single treatment response

Thread Tolerance Class:

6g external

Included Contact Quantity:

11 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.011 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-d0d-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Iso s and special acme

Specification Data:

81349-d0d-c-38999/46 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0