## NSN 5935-01-154-4660

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-154-4660 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight shape, flush mount **Overall Length:** 1.700 inches **Overall Height:** Between 3.060 inches and 3.090 inches **Overall Width:** Between 1.985 inches and 2.015 inches **Environmental Protection:** Corrosion resistant and thermal shock resistant and shock resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** Between 0.118 inches and 0.122 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 2.782 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.436 inches **Distance From Mounting Shoulder To Front Face:** Between 0.055 inches and 0.065 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 2 **Contact Position Arrangement Style:** "106, a106" all mating ends **Contact Removability:** Removable all mating ends single contact grouping Shell Type: Solid **Connector Locking Method:** Post jacksocket Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.190 inches

**Terminal Location:** 

Back all mating ends single contact grouping

**Contact Material:** 

Copper alloy all mating ends single contact grouping

## NSN 5935-01-154-4660

Electrical Receptacle Connector - Page 2 of 2



Contact Surface Treatment:
Gold all mating ends single contact grouping
Insert Material:
Plastic phenolic single mating end
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response all mating ends single contact grouping
Terminal Type:
Crimp all mating ends single contact grouping
Guide Design And Location:
Hexagon shape male post left-hand at 6 oclock and hexagon shape male post right-hand at 6 oclock
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416, type 2, class 1 federal specification single treatment response
Shell Material Specification:
Qq-a-591 federal specification single material response
Insert Material Specification:
Mil-m-14 military specification single material response single mating end
Included Contact Type:
Round socket all mating ends single contact grouping
Special Features:
Jackscrew type-female and location-center
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.212 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

A039b0

Fiig:

Mil-std (military Standard):

Mil-g-45204 spec.