Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-154-4660

Thread Class:	
2b	
Thread Direction:	
Right-hand	
Body Style:	
Straight shape, flush mount	
Overall Length:	
1.700 inches	
Overall Height:	
Between 3.060 inches and 3.090 inches	
Overall Width:	
Between 1.985 inches and 2.015 inches	
Environmental Protection:	
Corrosion resistant and thermal shock resistant and shock resistant and vibration resistant	
Unthreaded Mounting Hole Diameter:	
Between 0.118 inches and 0.122 inches	
Center To Center Distance Between Mounting Facilities Parallel To Height:	
2.782 inches	
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:	
1.436 inches	
Distance From Mounting Shoulder To Front Face:	
Between 0.055 inches and 0.065 inches	
Threaded Device Type:	
Coupling facility	
Mating End Quantity:	
2	
Contact Position Arrangement Style:	
"106, a106" all mating ends	
Contact Removability:	
Removable all mating ends single contact grouping	
Shell Type:	
Solid	
Connector Locking Method:	
Post jacksocket	
Thready Qty Per Inch (tpi):	
24	
Thread Size:	
0.190 inches	
Terminal Location:	
Back all mating ends single contact grouping	
Contact Material:	
Copper alloy all mating ends single contact grouping	



Contact Surface Treatment: Gold all mating ends single contact grouping **Insert Material:** Plastic phenolic single mating end **Contact Surface Treatment Specification:** Mil-g-45204 military specification single treatment response all mating ends single contact grouping **Terminal Type:** Crimp all mating ends single contact grouping **Guide Design And Location:** Hexagon shape male post left-hand at 6 oclock and hexagon shape male post right-hand at 6 oclock Shell Material: Aluminum alloy **Shell Surface Treatment:** Cadmium Shell Surface Treatment Specification: Qq-p-416, type 2, class 1 federal specification single treatment response **Shell Material Specification:** Qq-a-591 federal specification single material response **Insert Material Specification:** Mil-m-14 military specification single material response single mating end **Included Contact Type:** Round socket all mating ends single contact grouping **Special Features:** Jackscrew type-female and location-center **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.212 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unc Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.