

View Online at <https://aerobasegroup.com/nsn/5935-01-154-6240>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, flange mount

Overall Length:

0.600 inches

Overall Height:

0.580 inches

Environmental Protection:

Corrosion resistant and humidity resistant and shock proof and vibration proof

Unthreaded Mounting Hole Diameter:

Between 0.100 inches and 0.105 inches

Distance Between Mounting Facility Centers:

0.428 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

Nonstd single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

Thready Qty Per Inch (tpi):

36

Thread Size:

0.250 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and copper single mating end single contact grouping

Insert Material:

Plastic polytetrafluoroethylene single mating end

Contact Surface Treatment Specification:

Mil-g-45204, ty ii, grade b, cl 2 military specification 1st treatment response single mating end single contact grouping and mil-c-14550 class 4 military specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Contact Material Specification:

Qq-c-533, condition h federal specification single material response single mating end single contact grouping

Shell Material:

Stainless steel

Shell Surface Treatment:

Passivate

Shell Surface Treatment Specification:

Qq-p-35, ty i, ii or iii federal specification single treatment response

Shell Material Specification:

Qq-s-764, series 303, condition a federal specification single material response

Insert Material Specification:

Mil-p-19468 military specification single material response single mating end

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.005 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Uns

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.