NSN 5935-01-154-7267

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-154-7267

Body Style:
Straight shape
Overall Length:
4.595 inches
Overall Height:
0.670 inches
Overall Width:
0.590 inches
Unthreaded Mounting Hole Diameter:
0.120 inches
Distance Between Mounting Facility Centers:
4.275 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
3.0 single mating end single contact grouping
Polarization Method:
Mating end
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Contact Surface Treatment:
Contact Surface Treatment: Gold single mating end single contact grouping
Contact Surface Treatment: Gold single mating end single contact grouping Insert Material:
Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Plastic polyamide single mating end
Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Plastic polyamide single mating end Terminal Type:
Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Plastic polyamide single mating end Terminal Type: Wire wrap single mating end single contact grouping
Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Plastic polyamide single mating end Terminal Type: Wire wrap single mating end single contact grouping Contact Material Specification:
Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Plastic polyamide single mating end Terminal Type: Wire wrap single mating end single contact grouping Contact Material Specification: Qq-c-530 federal specification single material response single mating end single contact grouping
Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Plastic polyamide single mating end Terminal Type: Wire wrap single mating end single contact grouping Contact Material Specification: Qq-c-530 federal specification single material response single mating end single contact grouping Insert Material Specification:
Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Plastic polyamide single mating end Terminal Type: Wire wrap single mating end single contact grouping Contact Material Specification: Qq-c-530 federal specification single material response single mating end single contact grouping Insert Material Specification: Mil-p-46161 military specification single material response single mating end
Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Plastic polyamide single mating end Terminal Type: Wire wrap single mating end single contact grouping Contact Material Specification: Qq-c-530 federal specification single material response single mating end single contact grouping Insert Material Specification: Mil-p-46161 military specification single material response single mating end Included Contact Quantity:
Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Plastic polyamide single mating end Terminal Type: Wire wrap single mating end single contact grouping Contact Material Specification: Qq-c-530 federal specification single material response single mating end single contact grouping Insert Material Specification: Mil-p-46161 military specification single material response single mating end Included Contact Quantity: 66 single mating end single contact grouping

Contact surfaces gold

NSN 5935-01-154-7267

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Weight:
0.066 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-p-46161 spec.