

View Online at <https://aerobasegroup.com/nsn/5935-01-155-1159>

**Body Style:**

Rectangular shape

**Overall Length:**

2.090 inches

**Overall Height:**

0.320 inches

**Body Width:**

Between 0.281 inches and 0.294 inches

**Environmental Protection:**

Moisture resistant and vibration resistant and shock resistant

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

2 rows of contacts non-inserted board single mating end

**Contact Removability:**

Removable single mating end all contact groupings

**Contact Maximum Current Rating In Amps:**

3.0 single mating end all contact groupings

**Connector Locking Method:**

Friction

**Terminal Location:**

Back single mating end all contact groupings

**Contact Material:**

Copper alloy 172 single mating end all contact groupings

**Contact Surface Treatment:**

Gold single mating end all contact groupings and nickel single mating end all contact groupings

**Insert Material:**

Plastic diallyl phthalate single mating end and glass fiber single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204 type 2, cl 0 military specification 1st treatment response single mating end all contact groupings and qq-n-290 cl 2 federal specification 2nd treatment response single mating end all contact groupings

**Terminal Type:**

Tab, solder lug single mating end all contact groupings

**Contact Material Specification:**

Qq-c-533 1/4 hard federal specification single material response single mating end all contact groupings

**Insert Material Specification:**

Mil-m-14 military specification all material responses single mating end

**Included Contact Quantity:**

14 single mating end 1st contact grouping

**Included Contact Type:**

Flat socket single mating end all contact groupings

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.028 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.