## NSN 5935-01-155-1176

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-155-1176

Body Style:
Straight type
Overall Width:
0.200 inches
Environmental Protection:
Heat resistant and cold resistant
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic polyester single mating end and glass fiber single mating end
Contact Surface Treatment Specification:
Mil-g-45204 military specification 1st treatment response single mating end single contact grouping
Terminal Type:
Pin single mating end single contact grouping
Contact Material Specification:
Qq-b-750 comp a federal specification single material response single mating end single contact grouping
Included Contact Quantity:
32 single mating end single contact grouping
Included Contact Type:
Flat pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.032 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5935-01-155-1176

Electrical Receptacle Connector - Page 2 of 2



_						
11	em)	 tor	172	+ 1	nn	

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.