NSN 5935-01-155-2463

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-155-2463

| Thread Class: |
|---|
| 2a |
| Thread Direction: |
| Right-hand |
| Body Style: |
| Straight shape, external coupling |
| Overall Length: |
| 0.547 inches |
| Overall Diameter: |
| 1.516 inches |
| Threaded Device Type: |
| Coupling facility |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 28-22 single mating end |
| Contact Removability: |
| Nonremovable single mating end all contact groupings |
| Polarization Method: |
| Keyway or multiple keyway |
| Insert Position In Deg: |
| 0.0 |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Externally threaded shell |
| Thready Qty Per Inch (tpi): |
| 18 |
| Thread Size: |
| 1.624 inches |
| Terminal Location: |
| Back single mating end all contact groupings |
| Contact Material: |
| Copper alloy single mating end all contact groupings |
| Contact Surface Treatment: |
| Gold single mating end all contact groupings and silver single mating end all contact groupings |
| Insert Material: |
| Rubber silicone class q single mating end |
| Terminal Type: |
| Solder well single mating end all contact groupings |
| Shell Material: |
| Aluminum alloy |
| Shell Material: |

NSN 5935-01-155-2463Electrical Plug Connector - Page 2 of 2



| Shell Surface Treatment: |
|---|
| Cadmium |
| Included Contact Quantity: |
| 3 single mating end 2nd contact grouping |
| Included Contact Type: |
| Round pin single mating end all contact groupings |
| Precious Material And Location: |
| Contact surfaces gold |
| Precious Material And Weight: |
| 0.030 gold grains, troy |
| Precious Material: |
| Gold |
| Thread Series Designator: |
| Unef |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |