## NSN 5935-01-155-5544

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-155-5544

**Body Style:** 

Right angle type

**Overall Length:** 

2.980 inches

**Body Height:** 

0.375 inches

**Unthreaded Mounting Hole Diameter:** 

Between 0.096 inches and 0.101 inches

**Distance Between Mounting Facility Centers:** 

2.650 inches

**Mating End Quantity:** 

.

**Contact Position Arrangement Style:** 

2 rows of contacts non-inserted board single mating end

**Contact Removability:** 

Removable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:** 

5.0 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:** 

1300.0 single mating end single contact grouping

**Polarization Method:** 

Mating end

**Connector Locking Method:** 

Friction

**Terminal Location:** 

Side single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Tin single mating end single contact grouping

**Insert Material:** 

Plastic single mating end

**Contact Surface Treatment Specification:** 

Mil-t-10727 military specification single treatment response single mating end single contact grouping

**Terminal Type:** 

Pin single mating end single contact grouping

**Contact Material Specification:** 

Qq-b-626 federal specification single material response single mating end single contact grouping

**Insert Material Specification:** 

Mil-p-46161, grade b, class 15 military specification single material response single mating end

**Included Contact Quantity:** 

46 single mating end single contact grouping

## NSN 5935-01-155-5544

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Brush wire surface gold
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-t-10727 spec.