NSN 5935-01-155-6229

Electrical Receptacle Connector Body - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-155-6229 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.300 inches **Overall Height:** 1.250 inches **Overall Width:** 1.250 inches **Environmental Protection:** Moisture resistant and shock resistant and vibration resistant and salt water resistant **Unthreaded Mounting Hole Diameter:** 0.120 inches **Center To Center Distance Between Mounting Facilities Parallel To Height:** 0.969 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.969 inches **Distance From Mounting Shoulder To Front Face:** Between 0.760 inches and 0.800 inches **Threaded Device Type:** Back shell **Mating End Quantity: Contact Position Arrangement Style:** 19p single mating end **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 95.0 and 145.0 and 220.0 and 265.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin Thready Qty Per Inch (tpi): 20 **Thread Size:**

1.000 inches

Insert Material:

Plastic phenolic mineral filled single mating end

NSN 5935-01-155-6229

Electrical Receptacle Connector Body - Page 2 of 2



Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification single treatment response
Shell Material Specification:
Qq-a-367 federal specification single material response
Insert Material Specification:
Mil-m-14, ty mfh military specification single material response single mating end
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-m-14 spec.