## NSN 5935-01-155-7483

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-155-7483 **Thread Class:** 2a and 2a **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 3.370 inches **Overall Diameter:** 2.120 inches **Distance From Mounting Shoulder To Front Face:** 1.370 inches **Threaded Device Type:** Back shell and coupling facility **Mating End Quantity: Contact Removability:** Removable single mating end single contact grouping **Shell Type:** Solid **Connector Locking Method:** Externally threaded shell Thready Qty Per Inch (tpi): 12 and 12 **Thread Size:** 2.000 inches and 1.250 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Rubber synthetic single mating end **Contact Surface Treatment Specification:** Mil-g-45204 military specification single treatment response single mating end single contact grouping **Terminal Type:** Crimp single mating end single contact grouping **Shell Material:** Aluminum **Shell Surface Treatment:** Anodize

## NSN 5935-01-155-7483

Electrical Receptacle Connector - Page 2 of 2



## **Shell Surface Treatment Specification:** Mil-a-8625, type 2 military specification single treatment response **Included Contact Quantity:** 30 single mating end single contact grouping **Included Contact Type:** Round socket single mating end single contact grouping **Special Features:** Solder flange mtd **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.030 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Un and unf Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.