NSN 5935-01-155-9620

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-155-9620

Thread Class:
2b
Thread Direction:
Right-hand
Body Style:
Straight shape, internal coupling
Overall Length:
0.830 inches
Environmental Protection:
Vibration resistant and shock resistant and salt water resistant and moisture resistant
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
Sma single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling ring
Connector Cable Strain Relief Method:
Compression nut
Radio Frequency Type Contact Characteristic Impedance In Ohms:
50.0 single mating end single contact grouping
Thready Qty Per Inch (tpi):
36
Thread Size:
0.250 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and copper single mating end single contact grouping
Insert Material:
Plastic polytetrafluoroethylene single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 2, cl 1, grade c military specification 1st treatment response single mating end single contact grouping and mil-c-14550, c
4 military specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

NSN 5935-01-155-9620

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.

Electrical Plug Connector - Page 2 of 2



Contact Material Specification:
Qq-c-533, cond h federal specification single material response single mating end single contact grouping
Shell Material:
Stainless steel
Shell Surface Treatment:
Passivate
Shell Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Shell Material Specification:
Qq-s-764, cl 303, cond a federal specification single material response
Insert Material Specification:
Mil-p-19468 military specification single material response single mating end
Included Contact Quantity:
1 single mating end single contact grouping
Included Contact Type:
Coaxial socket single mating end single contact grouping
Precious Material And Location:
Contact surface gold
Precious Material And Weight:
0.005 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Uns
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: