

View Online at <https://aerobasegroup.com/nsn/5935-01-156-7750>

Body Style:

Straight shape, internal coupling w/backshell

Overall Length:

5.250 inches

Overall Diameter:

1.562 inches

Environmental Protection:

Moisture proof and salt water resistant and vibration proof

Mating End Quantity:

1

Contact Position Arrangement Style:

14-19 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Bayonet latch

Terminal Location:

Back single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Contact Surface Treatment Specification:

Mil-g-45204, type 1, class 1, grade c military specification 1st treatment response single mating end single contact grouping and qq-n-290, grade e federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416, type 2, class 3 federal specification single treatment response

Shell Material Specification:

Qq-a-591 federal specification single material response

Included Contact Quantity:

19 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.019 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.