NSN 5935-01-156-7755

Electrical Receptacle Connector - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5935-01-156-7755 **Thread Class:** 2a and 2b **Thread Direction:** Right-hand **Body Style:** Rectangular shape **Overall Length:** 2.281 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 1.969 inches **Overall Height:** 0.856 inches **Overall Width:** 1.125 inches **Environmental Protection:** Humidity resistant and shock resistant and thermal shock resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** 0.118 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.500 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 50 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 13.0 single mating end single contact grouping **Polarization Method:** Jackscrew Shell Type: Solid **Connector Locking Method:** Jackscrew-socket Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.138 inches

Terminal Location:

Back single mating end single contact grouping

NSN 5935-01-156-7755

Electrical Receptacle Connector - Page 2 of 3



Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 1, grade c military specification single treatment response single mating end single contact grouping
Criticality Code Justification:
Zzzy
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416, type 2, cl 1 federal specification single treatment response
Insert Material Specification:
Mil-m-14, ty sdg-f military specification single material response single mating end
Unable To Decode:
Unable to decode and unable to decode
Included Contact Quantity:
50 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Special Features:
Item must comply with requirements of defense supply center columbus production standard no. Lo3291
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.050 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Reference Number Differentiating Characteristics:
Areference number differentiating material will be in accordance with naval inventory control point activity hx quality control. Manufacturing
and testing specifications available at the dla icp
Shelf Life:
N/a
Unit Of Measure:

A039b0

No **Fiig:**

Demilitarization:

NSN 5935-01-156-7755

Electrical Receptacle Connector - Page 3 of 3



Mil-std (military Standard):

Mil-g-45204 spec.