

View Online at <https://aerobasegroup.com/nsn/5935-01-156-7759>

Body Style:

Right angle type

Overall Length:

6.090 inches

Overall Height:

0.640 inches

Overall Width:

0.385 inches

Environmental Protection:

Corrosion resistant

Unthreaded Mounting Hole Diameter:

Between 0.097 inches and 0.100 inches

Distance Between Mounting Facility Centers:

5.890 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Polarization Method:

Mating end

Connector Locking Method:

Friction

Terminal Location:

Side single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 1, grade c, cl 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290 federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Tab, solder lug single mating end single contact grouping

Contact Material Specification:

Qq-b-613, composition 2 federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-14, ty gdi-30f military specification single material response single mating end

Included Contact Quantity:

112 single mating end single contact grouping

Included Contact Type:

Flat pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.112 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.