

View Online at <https://aerobasegroup.com/nsn/5935-01-156-7777>

Body Style:

Rectangular shape

Overall Length:

0.838 inches

Overall Height:

0.100 inches

Body Width:

0.128 inches

Environmental Protection:

Shock resistant and vibration resistant and humidity resistant and salt water resistant

Mating End Quantity:

1

Contact Position Arrangement Style:

Nonstd single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

300.0 single mating end single contact grouping

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic polyamide single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 1 federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Wire wrap single mating end single contact grouping

Contact Material Specification:

Qq-b-626, comp 360 federal specification single material response single mating end single contact grouping or qq-b-613, comp 260 federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-20693, type 1 military specification single material response single mating end

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Special Features:

Solder flange mtd

Precious Material And Location:

Contact surface gold

Precious Material And Weight:

0.001 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-28754 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-c-28754/35 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.