

View Online at <https://aerobasegroup.com/nsn/5935-01-156-7800>

Thread Class:

2a and 2b and 2a

Thread Direction:

Right-hand and right-hand and right-hand

Body Style:

Rectangular shape

Overall Length:

3.875 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.500 inches

Overall Height:

0.706 inches

Overall Width:

2.000 inches

Unthreaded Mounting Hole Diameter:

0.150 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.875 inches

Threaded Device Type:

Coupling facility and mounting stud

Mating End Quantity:

1

Contact Position Arrangement Style:

25-104 single mating end

Polarization Method:

Jackscrew and polarization boss

Shell Type:

Solid

Connector Locking Method:

Jackscrew-socket

Thready Qty Per Inch (tpi):

32 and 32 and 40

Thread Size:

0.164 inches and 0.164 inches and 0.112 inches

Insert Material:

Plastic diallyl phthalate single mating end or plastic epoxy single mating end or plastic phenolic single mating end

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium and chromate and zinc

Shell Surface Treatment Specification:

Qq-p-416 type 2, cl 1 federal specification single treatment response

Insert Material Specification:

Mil-m-14, type sgd-f military specification single material response single mating end or mil-p-19833, type gdi-30 military specification single material response single mating end

Thread Series Designator:

Unc and unc and unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.