

View Online at https://aerobasegroup.com/nsn/5935-01-156-7800

Thread Class:
2a and 2b and 2a
Thread Direction:
Right-hand and right-hand and right-hand
Body Style:
Rectangular shape
Overall Length:
3.875 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
3.500 inches
Overall Height:
0.706 inches
Overall Width:
2.000 inches
Unthreaded Mounting Hole Diameter:
0.150 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.875 inches
Threaded Device Type:
Coupling facility and mounting stud
Mating End Quantity:
1
Contact Position Arrangement Style:
25-104 single mating end
Polarization Method:
Jackscrew and polarization boss
Shell Type:
Solid
Connector Locking Method:
Jackscrew-socket
Thready Qty Per Inch (tpi):
32 and 32 and 40
Thread Size:
0.164 inches and 0.164 inches and 0.112 inches
Insert Material:
Plastic diallyl phthalate single mating end or plastic epoxy single mating end or plastic phenolic single mating end
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate and zinc
Shell Surface Treatment Specification:
Qq-p-416 type 2, cl 1 federal specification single treatment response



Insert Material Specification:

Mil-m-14, type sdg-f military specification single material response single mating end or mil-p-19833, type gdi-30 military specification single material response single mating end

Thread Series Designator:

Unc and unc and unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.