

View Online at <https://aerobasegroup.com/nsn/5935-01-156-8628>

Body Style:

Rectangular shape

Overall Length:

0.440 inches

Overall Height:

0.320 inches

Body Width:

Between 0.281 inches and 0.294 inches

Environmental Protection:

Moisture resistant and vibration resistant and shock resistant

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Removable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

3.0 single mating end all contact groupings

Connector Locking Method:

Friction

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy 172 single mating end all contact groupings

Contact Surface Treatment:

Gold single mating end all contact groupings and nickel single mating end all contact groupings

Insert Material:

Plastic diallyl phthalate single mating end and glass fiber single mating end

Contact Surface Treatment Specification:

Mil-g-45204 type 2, cl 0 military specification 1st treatment response single mating end all contact groupings and qq-n-290 cl 2 federal specification 2nd treatment response single mating end all contact groupings

Terminal Type:

Tab, solder lug single mating end all contact groupings

Contact Material Specification:

Qq-c-533 1/4 hard federal specification single material response single mating end all contact groupings

Insert Material Specification:

Mil-m-14 military specification all material responses single mating end

Included Contact Quantity:

3 single mating end 2nd contact grouping

Included Contact Type:

Flat socket single mating end all contact groupings

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.006 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.