

View Online at <https://aerobasegroup.com/nsn/5935-01-157-2678>

Body Style:

Straight type

Overall Length:

3.650 inches

Overall Width:

0.490 inches

Environmental Protection:

Salt water resistant and cold resistant and heat resistant and vibration resistant and shock resistant

Unthreaded Mounting Hole Diameter:

Between 0.068 inches and 0.073 inches

Distance Between Mounting Facility Centers:

3.475 inches

Mating End Quantity:

1

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204 ty ii, cl 1, grade b military specification 1st treatment response single mating end single contact grouping and qq-n-290 cl 1, grade c or d federal specification 2nd treatment response single mating end single contact grouping

Contact Material Specification:

Qq-b-613 1/2 h federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-14 ty sdg-f military specification single material response single mating end

Included Contact Quantity:

128 single mating end single contact grouping

Included Contact Type:

Flat pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.128 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.