NSN 5935-01-157-2678

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-157-2678

Body Style: Straight type **Overall Length:** 3.650 inches Overall Width: 0.490 inches **Environmental Protection:** Salt water resistant and cold resistant and heat resistant and vibration resistant and shock resistant **Unthreaded Mounting Hole Diameter:** Between 0.068 inches and 0.073 inches **Distance Between Mounting Facility Centers:** 3.475 inches **Mating End Quantity: Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 3.0 single mating end single contact grouping **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and nickel single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Contact Surface Treatment Specification:** Mil-g-45204 ty ii, cl 1, grade b military specification 1st treatment response single mating end single contact grouping and qq-n-290 cl 1, grade c or d federal specification 2nd treatment response single mating end single contact grouping **Contact Material Specification:** Qq-b-613 1/2 h federal specification single material response single mating end single contact grouping **Insert Material Specification:** Mil-m-14 ty sdg-f military specification single material response single mating end **Included Contact Quantity:** 128 single mating end single contact grouping **Included Contact Type:** Flat pin single mating end single contact grouping **Precious Material And Location:**

0.128 gold grains, troy

Contact surfaces gold

Precious Material And Weight:

Precious Material:

Gold

NSN 5935-01-157-2678

Electrical Receptacle Connector - Page 2 of 2



N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A039b0	

Shelf Life:

Mil-std (military Standard):

Mil-g-45204 spec.