

View Online at https://aerobasegroup.com/nsn/5935-01-157-3460

Contact Position Arrangement Style: 20-27 single mating end Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Thready Qty Per Inch (tpi): 18 and 10 Thread Size: 1.125 inches and 1.250 inches Insert Material: Rubber single mating end Shell Material: Aluminum alloy Shell Surface Treatment: Anodize Thread Series Designator: Unef and double stub Shelf Life:	Thread C	lass:
Left-hand night-hand Body Style: Straight shape, internal coupling Overall Length: 1.735 inches Overall Diameter: 1.755 inches Environmental Protection: Waterproof and moisture proof and salt water resistant and vibration proof Threaded Device Type: Back shell and coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 20-27 single mating end Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Thready Qty Per Inch (tpi): 18 and 10 Thread Size: 1.125 inches and 1.250 inches Insert Material: Rubber single mating end Shell Material: Auminum alloy Shell Surface Treatment: Anodize Thread Series Designator: Unef and double stub Shelf Life: N/a	2a and 2b)
Body Style: Straight shape, internal coupling Overall Length: 1.735 inches Overall Diameter: 1.551 inches Environmental Protection: Waterproof and moisture proof and salt water resistant and vibration proof Threaded Device Type: Back shell and coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 20-27 single mating end Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Thread Yup Per Inch (tpi): 18 and 10 Thread Size: 1.125 inches and 1.250 inches Insert Material: Rubber single mating end Shell Material: Auuninum alloy Shell Surface Treatment: Anodize Thread Series Designator: Unef and double stub Shelf Life: N/a	Thread D	irection:
Straight shape, internal coupling Overall Length: 1.735 inches Overall Diameter: 1.551 inches Environmental Protection: Waterproof and moisture proof and salt water resistant and vibration proof Threaded Device Type: Back shell and coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 20-27 single mating end Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Thready Qty Per Inch (tpi): 18 and 10 Thread Size: 1.125 inches and 1.250 inches Insert Material: Rubber single mating end Shell Material: Aluminum alloy Shell Surface Treatment: Anodize Thread Series Designator: Unef and double stub Shelf Life: Na	Left-hand	and right-hand
Overall Length: 1.735 inches Overall Diameter: 1.551 inches Environmental Protection: Waterproof and moisture proof and salt water resistant and vibration proof Threaded Device Type: Back shell and coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 20-27 single mating end Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type: Solid Concetor Locking Method: Internally threaded coupling ring Thread Size: 1.125 inches and 1.250 inches Insert Material: Rubber single mating end Shell Material: Auminum alloy Shell Surface Treatment: Anodize Thread Sites Shell Surface Treatment: Anodize Thread Sube stub Shell Surface Treatment: Anodize Thread Sube stub Shell Surface Treatment: Anodize Thread Sube	Body Sty	le:
1.735 inches Overall Diameter: 1.551 inches Environmental Protection: Waterproof and moisture proof and salt water resistant and vibration proof Threaded Device Type: Back shell and coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 20-27 single mating end Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type: Solid Concetor Locking Method: Internally threaded coupling ring Thready Qty Per Inch (tpi): 18 and 10 Thread Size: 1.125 inches and 1.250 inches Insert Material: Rubber single mating end Shell Material: Rubber single mating end Shell Surface Treatment: Anodize Thread Stries Dief Liffe: Na	Straight s	hape, internal coupling
Overall Diameter: 1.551 inches Environmental Protection: Waterproof and moisture proof and salt water resistant and vibration proof Threaded Device Type: Back shell and coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 20-27 single mating end Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Thready Qty Per Inch (tpi): 18 and 10 Thread Size: 1.125 inches and 1.250 inches Insert Material: Rubber single mating end Shell Material: Aluminum alloy Shell Surface Treatment: Anodize Thread Series Designator: Unef and double stub Shelf Life: N/a	Overall L	ength:
 1.551 inches Environmental Protection: Waterproof and moisture proof and salt water resistant and vibration proof Threaded Device Type: Back shell and coupling facility Mating End Quantity: Mating End Quantity: Contact Position Arrangement Style: 20-27 single mating end Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Thread Size: 1.125 inches and 1.250 inches Insert Material: Rubber single mating end Shell Material: Aluminum alloy Shell Surface Treatment: Anodize Thread Size: Signator: Unef and double stub Shelf Life: N/a 	1.735 incl	les
Environmental Protection: Waterproof and moisture proof and salt water resistant and vibration proof Threaded Device Type: Back shell and coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 20-27 single mating end Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Thready Qty Per Inch (tpi): 18 and 10 Thread Size: 1.125 inches and 1.250 inches Insert Material: Rubber single mating end Shell Material: Aluminum alloy Shell Surface Treatment: Anodize Thread Series Designator: Unef and double stub Shelf Life: N/a	Overall D	iameter:
Waterproof and moisture proof and salt water resistant and vibration proof Threaded Device Type: Back shell and coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 20-27 single mating end Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Thready Qty Per Inch (tpi): 18 and 10 Thread Size: 1.125 inches and 1.250 inches Insert Material: Rubber single mating end Shell Material: Aluminum alloy Shell Surface Treatment: Anodize Thread Series Designator: Unef and double stub Shelf Life: N/a	1.551 incl	nes
Threaded Device Type: Back shell and coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 20-27 single mating end Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Thready Qty Per Inch (tpi): 18 and 10 Thread Size: 1.125 inches and 1.250 inches Insert Material: Rubber single mating end Shell Material: Aluminum alloy Shell Surface Treatment: Anodize Thread Series Designator: Unef and double stub Shelf Life: N/a	Environn	nental Protection:
Back shell and coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 20-27 single mating end Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Thready Qty Per Inch (tpi): 18 and 10 Thread Size: 1.125 inches and 1.250 inches Insert Material: Rubber single mating end Shell Material: Aluminum alloy Shell Surface Treatment: Anodize Thread Series Designator: Unef and double stub Shelf Life: N/a	Waterpro	of and moisture proof and salt water resistant and vibration proof
Mating End Quantity: 1 Contact Position Arrangement Style: 20-27 single mating end Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Thready Qty Per Inch (tpi): 18 and 10 Thread Size: 1.125 inches and 1.250 inches Insert Material: Rubber single mating end Shell Material: Aluminum alloy Shell Surface Treatment: Anodize Thread Series Designator: Unef and double stub Shelf Life: N/a	Threaded	I Device Type:
1 Contact Position Arrangement Style: 20-27 single mating end Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Thready Qty Per Inch (tpi): 18 and 10 Thread Size: 1.125 inches and 1.250 inches Insert Material: Rubber single mating end Shell Material: Aluminum alloy Shell Surface Treatment: Anodize Thread Series Designator: Unef and double stub Shelf Life: N/a	Back shel	I and coupling facility
Contact Position Arrangement Style: 20-27 single mating end Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Thready Qty Per Inch (tpi): 18 and 10 Thread Size: 1.125 inches and 1.250 inches Insert Material: Rubber single mating end Shell Material: Aluminum alloy Shell Surface Treatment: Anodize Thread Series Designator: Unef and double stub Shelf Life: N/a	Mating E	nd Quantity:
20-27 single mating end Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Thready Qty Per Inch (tpi): 18 and 10 Thread Size: 1.125 inches and 1.250 inches Insert Material: Rubber single mating end Shell Material: Aluminum alloy Shell Surface Treatment: Anodize Thread Series Designator: Unef and double stub Shelf Life: N/a	1	
Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Thready Qty Per Inch (tpi): 18 and 10 Thread Size: 1.125 inches and 1.250 inches Insert Material: Rubber single mating end Shell Material: Aluminum alloy Shell Surface Treatment: Anodize Thread Series Designator: Unef and double stub Shelf Life: N/a	Contact I	Position Arrangement Style:
Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Thready Qty Per Inch (tpi): 18 and 10 Thread Size: 1.125 inches and 1.250 inches Insert Material: Rubber single mating end Shell Material: Aluminum alloy Shell Surface Treatment: Anodize Thread Series Designator: Unef and double stub Shelf Life: N/a	20-27 sing	gle mating end
Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Thready Qty Per Inch (tpi): 18 and 10 Thread Size: 1.125 inches and 1.250 inches Insert Material: Rubber single mating end Shell Material: Aluminum alloy Shell Surface Treatment: Anodize Thread Series Designator: Unef and double stub Shelf Life: N/a	Polarizat	ion Method:
0.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Thready Qty Per Inch (tpi): 18 and 10 Thread Size: 1.125 inches and 1.250 inches Insert Material: Alubber single mating end Shell Material: Aluminum alloy Shell Surface Treatment: Anodize Thread Series Designator: Unef and double stub Shelf Life: N/a	Keyway o	r multiple keyway
Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Thready Qty Per Inch (tpi): 18 and 10 Thread Size: 1.125 inches and 1.250 inches Insert Material: Rubber single mating end Shell Material: Aluminum alloy Shell Surface Treatment: Anodize Thread Series Designator: Unef and double stub Shelf Life: N/a	Insert Po	sition In Deg:
Solid Connector Locking Method: Internally threaded coupling ring Thready Qty Per Inch (tpi): 18 and 10 Thread Size: 1.125 inches and 1.250 inches Insert Material: Rubber single mating end Shell Material: Aluminum alloy Shell Surface Treatment: Anodize Thread Series Designator: Unef and double stub Shelf Life: N/a	0.0	
Connector Locking Method: Internally threaded coupling ring Thready Qty Per Inch (tpi): 18 and 10 Thread Size: 1.125 inches and 1.250 inches Insert Material: Rubber single mating end Shell Material: Aluminum alloy Shell Surface Treatment: Anodize Thread Series Designator: Unef and double stub Shelf Life: N/a	Shell Typ	ie:
Internally threaded coupling ring Thready Qty Per Inch (tpi): 18 and 10 Thread Size: 1.125 inches and 1.250 inches Insert Material: Rubber single mating end Shell Material: Aluminum alloy Shell Surface Treatment: Anodize Thread Series Designator: Unef and double stub Shelf Life: N/a	Solid	
Thready Qty Per Inch (tpi): 18 and 10 Thread Size: 1.125 inches and 1.250 inches Insert Material: Rubber single mating end Shell Material: Aluminum alloy Shell Surface Treatment: Anodize Thread Series Designator: Unef and double stub Shelf Life: N/a	Connecto	or Locking Method:
18 and 10 Thread Size: 1.125 inches and 1.250 inches Insert Material: Rubber single mating end Shell Material: Aluminum alloy Shell Surface Treatment: Anodize Thread Series Designator: Unef and double stub Shelf Life: N/a	Internally	threaded coupling ring
Thread Size: 1.125 inches and 1.250 inches Insert Material: Rubber single mating end Shell Material: Aluminum alloy Shell Surface Treatment: Anodize Thread Series Designator: Unef and double stub Shelf Life: N/a	Thready	Qty Per Inch (tpi):
1.125 inches and 1.250 inches Insert Material: Rubber single mating end Shell Material: Aluminum alloy Shell Surface Treatment: Anodize Thread Series Designator: Unef and double stub Shelf Life: N/a	18 and 10)
Insert Material: Rubber single mating end Shell Material: Aluminum alloy Shell Surface Treatment: Anodize Thread Series Designator: Unef and double stub Shelf Life: N/a	Thread S	ize:
Rubber single mating end Shell Material: Aluminum alloy Shell Surface Treatment: Anodize Thread Series Designator: Unef and double stub Shelf Life: N/a	1.125 incl	nes and 1.250 inches
Shell Material: Aluminum alloy Shell Surface Treatment: Anodize Thread Series Designator: Unef and double stub Shelf Life: N/a	Insert Ma	terial:
Aluminum alloy Shell Surface Treatment: Anodize Thread Series Designator: Unef and double stub Shelf Life: N/a	Rubber si	ngle mating end
Shell Surface Treatment: Anodize Thread Series Designator: Unef and double stub Shelf Life: N/a	Shell Mat	erial:
Anodize Thread Series Designator: Unef and double stub Shelf Life: N/a	Aluminum	alloy
Thread Series Designator: Unef and double stub Shelf Life: N/a	Shell Sur	face Treatment:
Unef and double stub Shelf Life: N/a	Anodize	
Shelf Life: N/a	Thread S	eries Designator:
N/a	Unef and	double stub
	Shelf Life):
Unit Of Measure:	N/a	
	Unit Of N	leasure:



Demilitarization:

No

Fiig:

A039b0