Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-157-5715

View Online at https://aerobasegroup.com/nsn/5935-01-157-5715
Body Style:
Straight type
Overall Length:
1.490 inches
Overall Width:
0.245 inches
Environmental Protection:
Shock resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
0.078 inches
Distance Between Mounting Facility Centers:
1.350 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
1 row of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Mating end
Connector Locking Method:
Friction
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Tab, solder lug single mating end single contact grouping
Contact Material Specification:
Qq-b-750, comp a federal specification single material response single mating end single contact grouping
Insert Material Specification:
Mil-m-14f, type sdgf military specification single material response single mating end
Included Contact Quantity:
22 single mating end single contact grouping
Included Contact Type:
Hermaphrodite single mating end single contact grouping



Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.022 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14f spec.