

View Online at <https://aerobasegroup.com/nsn/5935-01-157-6641>

**Thread Class:**

2b

**Thread Direction:**

Right-hand

**Body Style:**

Right angle type

**Overall Length:**

5.100 inches

**Distance Between Mounting Facility Centers:**

4.850 inches

**Threaded Device Type:**

Mounting hole

**Mating End Quantity:**

1

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

3.0 single mating end single contact grouping

**Polarization Method:**

2 polarization posts

**Shell Type:**

Solid

**Connector Locking Method:**

Friction

**Thready Qty Per Inch (tpi):**

40

**Thread Size:**

0.112 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:**

Plastic polyamide single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204 military specification 1st treatment response single mating end single contact grouping

**Terminal Type:**

Pin single mating end single contact grouping

**Contact Material Specification:**

Qq-b-613 comp 2 federal specification single material response single mating end single contact grouping

**Guide Design And Location:**

D shape pin right-hand at 12 o'clock

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Chromate

**Shell Surface Treatment Specification:**

Mil-c-5541 cl 1a military specification single treatment response

**Shell Material Specification:**

Qq-a-250/11 federal specification single material response

**Included Contact Quantity:**

75 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.075 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.