NSN 5935-01-157-7168

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-157-7168

Body Style: Right angle type Overall Length: 94.0 millimeters Overall Width: 15.5 millimeters Body Height: 8.6 millimeters Unthreaded Mounting Hole Diameter: 2.5 millimeters Distance Between Mounting Facility Centers: 88.9 millimeters Mating End Quantity: 1
Overall Length: 94.0 millimeters Overall Width: 15.5 millimeters Body Height: 8.6 millimeters Unthreaded Mounting Hole Diameter: 2.5 millimeters Distance Between Mounting Facility Centers: 88.9 millimeters Mating End Quantity:
94.0 millimeters Overall Width: 15.5 millimeters Body Height: 8.6 millimeters Unthreaded Mounting Hole Diameter: 2.5 millimeters Distance Between Mounting Facility Centers: 88.9 millimeters Mating End Quantity:
Overall Width: 15.5 millimeters Body Height: 8.6 millimeters Unthreaded Mounting Hole Diameter: 2.5 millimeters Distance Between Mounting Facility Centers: 88.9 millimeters Mating End Quantity:
15.5 millimeters Body Height: 8.6 millimeters Unthreaded Mounting Hole Diameter: 2.5 millimeters Distance Between Mounting Facility Centers: 88.9 millimeters Mating End Quantity:
Body Height: 8.6 millimeters Unthreaded Mounting Hole Diameter: 2.5 millimeters Distance Between Mounting Facility Centers: 88.9 millimeters Mating End Quantity:
8.6 millimeters Unthreaded Mounting Hole Diameter: 2.5 millimeters Distance Between Mounting Facility Centers: 88.9 millimeters Mating End Quantity:
Unthreaded Mounting Hole Diameter: 2.5 millimeters Distance Between Mounting Facility Centers: 88.9 millimeters Mating End Quantity:
2.5 millimeters Distance Between Mounting Facility Centers: 88.9 millimeters Mating End Quantity:
Distance Between Mounting Facility Centers: 88.9 millimeters Mating End Quantity:
88.9 millimeters Mating End Quantity:
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
300.0 single mating end single contact grouping
Polarization Method:
Mating end
Connector Locking Method:
Friction
Terminal Location:
Side single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Nickel single mating end single contact grouping and gold single mating end single contact grouping
Insert Material:
Plastic polyester single mating end
Terminal Type:
Solder stud single mating end single contact grouping
Included Contact Quantity:
Included Contact Quantity: 64 single mating end single contact grouping
64 single mating end single contact grouping
64 single mating end single contact grouping Included Contact Type:
64 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping

--

NSN 5935-01-157-7168

Electrical Receptacle Connector - Page 2 of 2



Demilitarization:

No

Fiig:

A039b0