

View Online at <https://aerobasegroup.com/nsn/5935-01-157-7825>

Thread Class:

2b

Thread Direction:

Right-hand

Body Style:

Right angle type

Overall Length:

5.100 inches

Distance Between Mounting Facility Centers:

4.850 inches

Threaded Device Type:

Mounting hole

Mating End Quantity:

1

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Polarization Method:

2 polarization posts

Shell Type:

Solid

Connector Locking Method:

Friction

Thready Qty Per Inch (tpi):

40

Thread Size:

0.112 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic polyamide single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification 1st treatment response single mating end single contact grouping

Terminal Type:

Pin single mating end single contact grouping

Contact Material Specification:

Qq-b-613 comp 2 federal specification single material response single mating end single contact grouping

Guide Design And Location:

D shape pin right-hand at 11 o'clock

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Chromate

Shell Surface Treatment Specification:

Mil-c-5541 cl 1a military specification single treatment response

Shell Material Specification:

Qq-a-250/11 federal specification single material response

Included Contact Quantity:

75 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.075 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.