

View Online at https://aerobasegroup.com/nsn/5935-01-157-9570

Thread C	
2a and 2b	
Thread D	irection:
Left-hand	and right-hand
Body Sty	le:
Straight sl	nape, internal coupling
Overall L	ength:
1.735 inch	les
Overall D	iameter:
1.551 inch	les
Environm	ental Protection:
Waterproc	of and moisture proof and salt water resistant and vibration proof
Threaded	Device Type:
Back shel	and coupling facility
Mating Er	nd Quantity:
1	
Contact F	Position Arrangement Style:
20-4 singl	e mating end
Polarizati	on Method:
Keyway o	r multiple keyway
Insert Po	sition In Deg:
315.0	
Shell Typ	e:
Solid	
Connecto	r Locking Method:
Internally	threaded coupling ring
Thready (Qty Per Inch (tpi):
18 and 10	
Thread Si	ze:
1.125 inch	ies and 1.250 inches
Insert Ma	terial:
Rubber si	ngle mating end
Shell Mat	erial:
Aluminum	alloy
Shell Sur	face Treatment:
Anodize	
Thread Se	eries Designator:
Unef and	double stub
Shelf Life	:
N/a	
Unit Of M	easure:



Demilitarization:

No

Fiig:

A039b0