

View Online at <https://aerobasegroup.com/nsn/5935-01-157-9964>

**Thread Class:**

2b

**Thread Direction:**

Right-hand

**Body Style:**

Angle, shape, internal coupling

**Overall Length:**

2.000 inches

**Overall Height:**

1.218 inches

**Overall Diameter:**

0.650 inches

**Environmental Protection:**

Shock proof and vibration proof

**Cable Entrance Diameter:**

0.160 inches

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

Qnc single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

500.0 single mating end single contact grouping

**Shell Type:**

Solid

**Connector Locking Method:**

Internally threaded coupling nut

**Connector Cable Strain Relief Method:**

Compression nut

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

50.0 single mating end single contact grouping

**Thready Qty Per Inch (tpi):**

20

**Thread Size:**

0.500 inches

**Terminal Location:**

Side single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2, cl 2 military specification single treatment response single mating end single contact grouping

**Terminal Type:**

Solder well single mating end single contact grouping

**Shell Material:**

Steel

**Included Contact Quantity:**

1 single mating end single contact grouping

**Included Contact Type:**

Coaxial pin single mating end single contact grouping

**Precious Material And Location:**

Contact surface gold

**Precious Material And Weight:**

0.005 gold grains, troy

**Precious Material:**

Gold

**Test Data Document:**

81349-mil-c-39012 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Double stub

**Specification Data:**

81349-mil-c-39012/83 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.