

View Online at <https://aerobasegroup.com/nsn/5935-01-157-9980>

Thread Class:

2a and 2a and 2a

Thread Direction:

Right-hand and right-hand and right-hand

Body Style:

Straight shape w/jackscrew

Overall Length:

Between 2.953 inches and 2.983 inches

Overall Width:

Between 1.085 inches and 1.125 inches

Environmental Protection:

Humidity resistant and shock resistant and thermal shock resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

0.147 inches

Distance Between Mounting Facility Centers:

2.670 inches

Threaded Device Type:

Coupling facility and back shell

Mating End Quantity:

1

Contact Position Arrangement Style:

90 single mating end

Polarization Method:

Polarization boss and guide pin/socket

Shell Type:

Solid

Connector Locking Method:

Screw

Thready Qty Per Inch (tpi):

32 and 32 and 40

Thread Size:

0.138 inches and 0.138 inches and 0.138 inches

Insert Material:

Plastic diallyl phthalate single mating end or plastic epoxy single mating end or plastic phenolic single mating end

Shell Material:

Steel comp 302 or steel comp 303 or steel comp 304

Shell Material Specification:

Qq-s-766, type 302 federal specification single material response

Insert Material Specification:

Mil-m-14, type sdg-f military specification single material response single mating end or mil-p-19833, type gdi-30 military specification single material response single mating end

Thread Series Designator:

Unc and unc and unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.