## NSN 5935-01-158-0369

Receptacle Dummy Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-158-0369 **Thread Class:** 2a and 2a **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.405 inches **Overall Diameter:** Between 1.735 inches and 1.766 inches **Environmental Protection:** Moisture proof and salt water resistant and vibration proof **Distance From Mounting Shoulder To Front Face:** Between 0.658 inches and 0.707 inches **Mounting Facility Thickness:** Between 0.062 inches and 0.187 inches **Threaded Device Type:** Back shell and mounting bushing **Mating End Quantity: Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin Thread Length: 0.290 inches Thready Qty Per Inch (tpi): 18 and 18 **Thread Size:** 1.062 inches and 1.250 inches **Shell Material:** Aluminum alloy 6061

**Shell Surface Treatment:** 

Cadmium

**Shell Surface Treatment Specification:** 

Qq-p-416 federal specification single treatment response

**Shell Material Specification:** 

Qq-a-591, a380 federal specification single material response or qq-a-367, t6 federal specification single material response

## NSN 5935-01-158-0369

Receptacle Dummy Connector - Page 2 of 2



<b>Bushing Accommodation Hole Shape:</b>
Round w/flat
Thread Series Designator:
Unef and unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A039b0