

View Online at <https://aerobasegroup.com/nsn/5935-01-158-0371>

**Body Style:**

Right angle type

**Overall Length:**

Between 3.750 inches and 3.770 inches

**Overall Height:**

0.700 inches

**Overall Width:**

0.305 inches

**Environmental Protection:**

Moisture resistant

**Unthreaded Mounting Hole Diameter:**

0.096 inches

**Distance Between Mounting Facility Centers:**

Between 3.350 inches and 3.370 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

2 rows of contacts non-inserted board single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

1.0 single mating end single contact grouping

**Polarization Method:**

Mating end

**Connector Locking Method:**

Friction

**Terminal Location:**

Side single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:**

Plastic polyester single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2, cl 0, grade c or d military specification 1st treatment response single mating end single contact grouping and qq-n-290 federal specification 2nd treatment response single mating end single contact grouping

**Terminal Type:**

Wire wrap single mating end single contact grouping

**Contact Material Specification:**

Qq-c-533 federal specification single material response single mating end single contact grouping

**Included Contact Quantity:**

60 single mating end single contact grouping

**Included Contact Type:**

Flat pin single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.060 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.