

View Online at <https://aerobasegroup.com/nsn/5935-01-158-0372>

Body Style:

Pcb, external coupling

Overall Length:

0.593 inches

Overall Height:

0.530 inches

Overall Width:

0.530 inches

Environmental Protection:

Shock proof and vibration proof

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.200 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.200 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

Nonstd single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

350.0 single mating end single contact grouping

Contact Maximum Frequency Rating:

10.0 kilohertz single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Spring friction

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

Terminal Location:

Side single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and copper single mating end single contact grouping

Insert Material:

Plastic fluorocarbon single mating end

Contact Surface Treatment Specification:

Mil-p-45204, type 2, cl 2 military specification 1st treatment response single mating end single contact grouping and mil-c-14450, cl 4 military specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Pin single mating end single contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response single mating end single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Gold and copper

Shell Surface Treatment Specification:

Mil-p-45204, type 2, cl 2 military specification 1st treatment response and mil-c-14450, cl 4 military specification 2nd treatment response

Shell Material Specification:

Qq-b-626 federal specification single material response

Insert Material Specification:

Mil-m-14077 military specification single material response single mating end

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial pin single mating end single contact grouping

Special Features:

Angle shaped

Precious Material And Location:

Contact and shell surfaces gold

Precious Material And Weight:

0.105 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-p-45204 spec.