

View Online at <https://aerobasegroup.com/nsn/5935-01-158-2412>

**Thread Class:**

2b and 2a and 2a

**Thread Direction:**

Right-hand and right-hand and right-hand

**Body Style:**

Rectangular shape center screwlock

**Overall Length:**

2.968 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.670 inches

**Overall Height:**

1.270 inches

**Overall Width:**

1.110 inches

**Environmental Protection:**

Moisture resistant and shock resistant and vibration resistant and salt water resistant

**Unthreaded Mounting Hole Diameter:**

0.147 inches

**Threaded Device Type:**

Coupling facility and back shell

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

90 single mating end

**Polarization Method:**

Polarization boss and guide pin/socket

**Shell Type:**

Solid

**Connector Locking Method:**

Post jacksocket

**Thready Qty Per Inch (tpi):**

32 and 32 and 40

**Thread Size:**

0.138 inches and 0.138 inches and 0.138 inches

**Insert Material:**

Plastic diallyl phthalate single mating end or plastic epoxy single mating end or plastic phenolic single mating end

**Shell Material:**

Steel comp 302 or steel comp 303 or steel comp 304

**Shell Surface Treatment:**

Passivate

**Shell Material Specification:**

Qq-s-766, type 302 federal specification single material response

**Insert Material Specification:**

Mil-m-14, type sdg-f military specification single material response single mating end

**Color:**

Green

**Thread Series Designator:**

Unc and unc and unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-m-14 spec.