

View Online at <https://aerobasegroup.com/nsn/5935-01-158-2413>

Thread Class:

2b and 2a and 2a

Thread Direction:

Right-hand and right-hand and right-hand

Body Style:

Rectangular shape center screwlock

Overall Length:

2.968 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.670 inches

Overall Height:

1.270 inches

Overall Width:

1.110 inches

Environmental Protection:

Moisture resistant and shock resistant and vibration resistant and salt water resistant

Unthreaded Mounting Hole Diameter:

0.147 inches

Threaded Device Type:

Coupling facility and back shell

Mating End Quantity:

1

Contact Position Arrangement Style:

90 single mating end

Polarization Method:

Polarization boss and guide pin/socket

Shell Type:

Solid

Connector Locking Method:

Post jacksocket

Thready Qty Per Inch (tpi):

32 and 32 and 40

Thread Size:

0.138 inches and 0.138 inches and 0.138 inches

Insert Material:

Plastic diallyl phthalate single mating end or plastic epoxy single mating end or plastic phenolic single mating end

Shell Material:

Steel comp 302 or steel comp 303 or steel comp 304

Shell Surface Treatment:

Passivate

Shell Material Specification:

Qq-s-766, type 302 federal specification single material response

Insert Material Specification:

Mil-m-14, type sdc-f military specification single material response single mating end

Color:

Green

Thread Series Designator:

Unc and unc and unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.