## NSN 5935-01-158-3722

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-158-3722

Thread Direction:

| Thread Direction:   |
|---|
| Right-hand  |
| Body Style:   |
| Straight shape, internal coupling                           |
| Overall Length:   |
| 36.5 millimeters  |
| Overall Diameter:   |
| 46.5 millimeters  |
| Environmental Protection:                                   |
| Moisture proof and salt water resistant and vibration proof |
| Threaded Device Type:                                       |
| Back shell  |
| Mating End Quantity:  |
| 1   |
| Contact Position Arrangement Style:                         |
| 23-55 single mating end                                     |
| Contact Removability:                                       |
| Removable single mating end single contact grouping         |
| Polarization Method:  |
| Keyway or multiple keyway                                   |
| Insert Position In Deg:                                     |
| 0.0   |
| Shell Type:   |
| Solid   |
| Connector Locking Method:                                   |
| Detent  |
| Thread Size:  |
| 34.0 millimeters  |
| Thread Pitch In Millimeters:                                |
| 1.00  |
| Terminal Location:  |
| Back single mating end single contact grouping              |
| Contact Material:   |
| Copper alloy single mating end single contact grouping      |
| Contact Surface Treatment:                                  |
| Gold single mating end single contact grouping              |
| Terminal Type:  |
| Crimp single mating end single contact grouping             |
| Shell Material:   |
| Aluminum alloy  |
| Shell Surface Treatment:                                    |

Cadmium

## **NSN 5935-01-158-3722**Electrical Plug Connector - Page 2 of 2

No Fiig: A039b0



| Shell Surface Treatment Specification:   |
|--|
| Qq-p-416 federal specification single treatment response   |
| Thread Tolerance Class:  |
| 6g external  |
| Included Contact Quantity:   |
| 55 single mating end single contact grouping   |
| Included Contact Type:   |
| Round socket single mating end single contact grouping   |
| Precious Material And Location:  |
| Contact surfaces gold  |
| Precious Material And Weight:  |
| 0.055 gold grains, troy  |
| Precious Material:   |
| Gold   |
| Test Data Document:  |
| 81349-dod-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain          |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                            |
| Thread Series Designator:  |
| Iso m  |
| Specification Data:  |
| 81349-dod-c-38999/46 government specification  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |