## NSN 5935-01-158-4407

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-158-4407

**Body Style:** 

Straight shape, external coupling w/backshell

**Overall Length:** 

34.1 millimeters

**Overall Height:** 

Between 39.1 millimeters and 40.2 millimeters

**Overall Width:** 

Between 39.1 millimeters and 40.2 millimeters

**Environmental Protection:** 

Moisture proof and salt water resistant and vibration proof

**Unthreaded Mounting Hole Diameter:** 

Between 3.1 millimeters and 3.5 millimeters

Center To Center Distance Between Mounting Facilities Parallel To Height:

31.7 millimeters

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

31.7 millimeters

**Distance From Mounting Shoulder To Front Face:** 

Between 19.2 millimeters and 20.8 millimeters

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

21-11 single mating end

**Contact Removability:** 

Removable single mating end single contact grouping

**Polarization Method:** 

Keyway or multiple keyway

**Insert Position In Deg:** 

0.0

Shell Type:

Solid

**Connector Locking Method:** 

Detent

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

**Terminal Type:** 

Crimp single mating end single contact grouping

**Shell Material:** 

Aluminum alloy

## NSN 5935-01-158-4407

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416 federal specification single treatment response
ncluded Contact Quantity:
11 single mating end single contact grouping
ncluded Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.011 gold grains, troy
Precious Material:
Gold
Test Data Document:
31349-dod-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
31349-dod-c-38999/42 government specification
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
4039b0