

View Online at <https://aerobasegroup.com/nsn/5935-01-158-9698>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape, external coupling

**Overall Length:**

1.060 inches

**Distance From Mounting Shoulder To Front Face:**

0.720 inches

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

2

**Contact Position Arrangement Style:**

Nonstd all mating ends

**Contact Removability:**

Nonremovable all mating ends single contact grouping

**Contact Maximum Frequency Rating:**

800.0 megahertz all mating ends single contact grouping

**Shell Type:**

Solid

**Connector Locking Method:**

Externally threaded shell

**End Application:**

Nimitz class cvn, wasp class lhd, ticonderoga class cg (47), forrestal class cv.

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.375 inches

**Contact Material:**

Copper alloy all mating ends single contact grouping

**Contact Surface Treatment:**

Tin all mating ends single contact grouping

**Insert Material:**

Plastic polypropylene all mating ends

**Criticality Code Justification:**

Feat

**Shell Material:**

Copper alloy

**Shell Surface Treatment:**

Tin

**Included Contact Quantity:**

1 all mating ends single contact grouping

**Included Contact Type:**

Coaxial socket all mating ends single contact grouping

**Special Features:**

Weapon system essential

**Thread Series Designator:**

Unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0