

View Online at <https://aerobasegroup.com/nsn/5935-01-158-9698>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

1.060 inches

Distance From Mounting Shoulder To Front Face:

0.720 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

2

Contact Position Arrangement Style:

Nonstd all mating ends

Contact Removability:

Nonremovable all mating ends single contact grouping

Contact Maximum Frequency Rating:

800.0 megahertz all mating ends single contact grouping

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

End Application:

Nimitz class cvn, wasp class lhd, ticonderoga class cg (47), forrestal class cv.

Thready Qty Per Inch (tpi):

32

Thread Size:

0.375 inches

Contact Material:

Copper alloy all mating ends single contact grouping

Contact Surface Treatment:

Tin all mating ends single contact grouping

Insert Material:

Plastic polypropylene all mating ends

Criticality Code Justification:

Feat

Shell Material:

Copper alloy

Shell Surface Treatment:

Tin

Included Contact Quantity:

1 all mating ends single contact grouping

Included Contact Type:

Coaxial socket all mating ends single contact grouping

Special Features:

Weapon system essential

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0