NSN 5935-01-158-9700

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-158-9700 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** Between 1.217 inches and 1.223 inches **Overall Height:** 1.562 inches **Overall Width:** 1.562 inches **Unthreaded Mounting Hole Diameter:** 0.120 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.250 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.250 inches **Distance From Mounting Shoulder To Front Face:** Between 0.630 inches and 0.636 inches **Threaded Device Type:** Back shell **Mating End Quantity: Contact Position Arrangement Style:** 22-35 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 400.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 550.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 80.0 Shell Type: Solid **Connector Locking Method:**

18

Bayonet pin

Thready Qty Per Inch (tpi):

NSN 5935-01-158-9700

Electrical Receptacle Connector - Page 2 of 2



Thread Size:
1.312 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic epoxy single mating end
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum
Shell Surface Treatment:
Nickel
Included Contact Quantity:
100 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.100 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.