Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-158-9814

Body Style:
Straight shape, flush mount
Overall Length:
1.326 inches
Overall Height:
Between 1.997 inches and 2.027 inches
Overall Width:
Between 1.985 inches and 2.015 inches
Environmental Protection:
Humidity resistant and salt water resistant and shock resistant and thermal shock resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
Between 0.115 inches and 0.125 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 1.715 inches and 1.725 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 1.432 inches and 1.442 inches
Distance From Mounting Shoulder To Front Face:
Between 0.055 inches and 0.065 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
40 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
3 polarization posts
Shell Type:
Solid
Connector Locking Method:
Friction
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end or plastic epoxy single mating end or plastic phenolic single mating end
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping



Shell Material: Aluminum alloy **Shell Surface Treatment:** Cadmium and chromate **Shell Surface Treatment Specification:** Qq-p-416 federal specification single treatment response **Shell Material Specification:** Qq-a-591 federal specification single material response or qq-a-367 federal specification single material response or qq-a-250 federal specification single material response **Insert Material Specification:** Mil-m-14 military specification single material response single mating end or 1288 bx mfr ref single material response single mating end **Included Contact Quantity:** 40 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.040 gold grains, troy **Precious Material:** Gold Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.