Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-159-1599

Thread Class:
2a and 2a
Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape, external coupling
Overall Length:
0.750 inches
Overall Diameter:
0.312 inches
Distance From Mounting Shoulder To Front Face:
0.450 inches
Mounting Facility Thickness:
0.093 inches
Threaded Device Type:
Coupling facility and mounting bushing
Mating End Quantity:
1
Contact Position Arrangement Style:
Sma single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
Radio Frequency Type Contact Characteristic Impedance In Ohms:
50.0 single mating end single contact grouping
Thready Qty Per Inch (tpi):
36 and 36
Thread Size:
0.250 inches and 0.250 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic polytetrafluoroethylene single mating end
Contact Surface Treatment Specification:

Mil-g-45204, type 1, class 2, grade c military specification single treatment response single mating end single contact grouping



## **Terminal Type:** Solder well single mating end single contact grouping **Contact Material Specification:** Qq-c-530 federal specification single material response single mating end single contact grouping or qq-c-533 federal specification single material response single mating end single contact grouping **Shell Material:** Stainless steel **Shell Surface Treatment:** Gold Shell Surface Treatment Specification: Mil-g-45204, type 1, class 1, grade c military specification single treatment response **Shell Material Specification:** Qq-s-763 federal specification single material response or qq-s-764 federal specification single material response **Insert Material Specification:** Mil-p-19468 military specification single material response single mating end **Included Contact Quantity:** 1 single mating end single contact grouping **Bushing Accommodation Hole Shape:** Round w/flat **Included Contact Type:** Coaxial socket single mating end single contact grouping **Precious Material And Location:** Contact and body surfaces gold **Precious Material And Weight:** 0.105 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Uns and uns Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.