Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-159-2595

### **Body Style:**

Angle shape, pcb type

### **Overall Length:**

4.900 inches

## **Overall Height:**

0.550 inches

**Overall Width:** 

0.540 inches

### **Environmental Protection:**

Vibration resistant and shock resistant and salt water resistant and humidity resistant and thermal shock resistant

## **Unthreaded Mounting Hole Diameter:**

0.120 inches

## **Distance Between Mounting Facility Centers:**

4.650 inches

### Mating End Quantity:

1

## **Contact Position Arrangement Style:**

3 rows of contacts non-inserted board single mating end

### Contact Removability:

Nonremovable single mating end single contact grouping

## **Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

# **Polarization Method:**

Guide pin/socket

## **Connector Locking Method:**

Friction

## **Operating Tempurature Rating:**

Between -65.0 degrees celsius and 125.0 degrees celsius

## **Terminal Location:**

Side single mating end single contact grouping

### **Contact Material:**

Copper alloy single mating end single contact grouping

## **Contact Surface Treatment:**

Gold single mating end single contact grouping

### **Insert Material:**

Plastic polyphenylene single mating end

## **Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response single mating end single contact grouping

## **Terminal Type:**

Pin single mating end single contact grouping

# **Contact Material Specification:**

Qq-c-530 federal specification single material response single mating end single contact grouping

Electrical Receptacle Connector - Page 2 of 2



**Guide Design And Location:** D shape socket left-hand at 12 oclock **Insert Material Specification:** Mil-m-24519 military specification single material response single mating end **Included Contact Quantity:** 122 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.122 gold grains, troy **Precious Material:** Gold **Specification Data:** 96214-803255 manufacturers specification control Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.