## NSN 5935-01-159-2596

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-159-2596

**Body Style:** 

Straight shape, flush mount

**Overall Length:** 

1.220 inches

**Overall Height:** 

Between 3.000 inches and 3.090 inches

**Overall Width:** 

Between 1.985 inches and 2.015 inches

**Environmental Protection:** 

Humidity resistant and salt water resistant and shock resistant and thermal shock resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:** 

Between 0.115 inches and 0.125 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 2.778 inches and 2.788 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 1.432 inches and 1.442 inches

**Distance From Mounting Shoulder To Front Face:** 

Between 0.055 inches and 0.065 inches

**Mating End Quantity:** 

2

**Contact Position Arrangement Style:** 

"106, a106" all mating ends

**Contact Removability:** 

Removable all mating ends single contact grouping

**Polarization Method:** 

3 polarization posts

Shell Type:

Solid

**Connector Locking Method:** 

Friction

**Terminal Location:** 

Back all mating ends single contact grouping

**Contact Material:** 

Copper alloy all mating ends single contact grouping

**Contact Surface Treatment:** 

Gold all mating ends single contact grouping

**Insert Material:** 

Plastic diallyl phthalate all mating ends or plastic epoxy all mating ends or plastic phenolic all mating ends

**Contact Surface Treatment Specification:** 

Mil-g-45204 military specification single treatment response all mating ends single contact grouping

Terminal Type:

Crimp all mating ends single contact grouping

## NSN 5935-01-159-2596

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate
Shell Surface Treatment Specification:
Qq-p-416 federal specification single treatment response
Shell Material Specification:
Qq-a-591 federal specification single material response or qq-a-367 federal specification single material response or qq-a-250 federal
specification single material response
Insert Material Specification:
Mil-m-14 military specification single material response all mating ends or 1288 bx mfr ref single material response all mating ends
Included Contact Type:
Round socket all mating ends single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.212 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.