# NSN 5935-01-159-3739

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-159-3739

Thread Class:
2a and 2b
Thread Direction:
Right-hand
Body Style:
Straight shape
Overall Length:
0.870 inches
Overall Height:
Between 0.560 inches and 0.610 inches
Overall Width:
0.343 inches
Environmental Protection:
Humidity resistant and salt water resistant and shock resistant and thermal shock resistant and vibration resistant
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
11 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Polarization Method:
Jackscrew
Connector Locking Method:
Jackscrew-socket
End Application:
Test set, countermeasures, an/usm-464
Thready Qty Per Inch (tpi):
56
Thread Size:  0.086 inches  Terminal Location:  Back single mating end single contact grouping  Contact Material:  Copper alloy single mating end single contact grouping  Contact Surface Treatment:  Gold single mating end single contact grouping and copper single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

# NSN 5935-01-159-3739

Electrical Plug Connector - Page 2 of 2



### **Contact Surface Treatment Specification:**

Mil-g-45204, ty ii, grade c, cl 1 military specification 1st treatment response single mating end single contact grouping and mil-c-14550 military specification 2nd treatment response single mating end single contact grouping

### **Terminal Type:**

Solder well single mating end single contact grouping

## **Contact Material Specification:**

Qq-b-626, alloy 360, 1/2 h federal specification single material response single mating end single contact grouping

### **Insert Material Specification:**

Mil-m-14, ty sdg-f or gdi-30f military specification single material response single mating end

## **Included Contact Quantity:**

11 single mating end single contact grouping

### **Included Contact Type:**

Round pin single mating end single contact grouping

### **Precious Material And Location:**

Contact surfaces gold

## **Precious Material And Weight:**

0.011 gold grains, troy

**Precious Material:** 

Gold

**Thread Series Designator:** 

Unc

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A039b0

## Mil-std (military Standard):

Mil-g-45204 spec.