

View Online at <https://aerobasegroup.com/nsn/5935-01-159-5514>

Thread Class:

2b

Thread Direction:

Right-hand

Body Style:

Straight shape, internal coupling

Overall Length:

0.910 inches

Overall Diameter:

0.312 inches

Environmental Protection:

Moisture resistant and corrosion resistant and thermal shock resistant and vibration resistant

Threaded Device Type:

Coupling facility

Mating End Quantity:

2

Contact Position Arrangement Style:

Sma all mating ends

Contact Removability:

Nonremovable all mating ends single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

335.0 all mating ends single contact grouping

Contact Maximum Frequency Rating:

18000.0 megahertz all mating ends single contact grouping

Shell Type:

Solid

Connector Locking Method:

Internally threaded coupling nut

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 all mating ends single contact grouping

Thread Length:

0.130 inches

Thread Qty Per Inch (tpi):

36

Thread Size:

0.250 inches

Contact Material:

Copper alloy all mating ends single contact grouping

Contact Surface Treatment:

Gold all mating ends single contact grouping

Contact Surface Treatment Specification:

Mil-g-45204, type 1, class 2, grade c military specification single treatment response all mating ends single contact grouping

Shell Material:

Stainless steel

Included Contact Quantity:

1 all mating ends single contact grouping

Included Contact Type:

Coaxial pin all mating ends single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.005 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-55339 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns

Specification Data:

81349-mil-c-55339/29 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.