

View Online at <https://aerobasegroup.com/nsn/5935-01-160-6986>

Thread Class:

2a and 2b

Thread Direction:

Left-hand and right-hand

Body Style:

Straight shape, internal coupling

Overall Length:

Between 1.639 inches and 1.660 inches

Overall Diameter:

1.469 inches

Environmental Protection:

Thermal shock resistant and moisture resistant and salt water resistant and shock resistant and vibration resistant

Threaded Device Type:

Back shell and coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

16-10 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Thready Qty Per Inch (tpi):

20 and 10

Thread Size:

1.000 inches and 1.125 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic single mating end

Contact Surface Treatment Specification:

Mil-g-45204 type 1, cl 1 military specification single treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium and nickel

Shell Surface Treatment Specification:

Qq-p-416 ty ii federal specification 1st treatment response and qq-n-290 federal specification 2nd treatment response

Included Contact Quantity:

3 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.015 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-22992 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef and double stub

Specification Data:

96906-ms17344 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.