

View Online at <https://aerobasegroup.com/nsn/5935-01-160-6992>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

1.243 inches

Overall Diameter:

Between 1.609 inches and 1.641 inches

Environmental Protection:

Moisture proof and salt water resistant and vibration proof

Distance From Mounting Shoulder To Front Face:

Between 0.910 inches and 0.920 inches

Mounting Facility Thickness:

Between 0.062 inches and 0.125 inches

Threaded Device Type:

Back shell and mounting bushing

Mating End Quantity:

1

Contact Position Arrangement Style:

15-97 single mating end

Contact Removability:

Removable single mating end all contact groupings

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

326.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Thread Length:

0.219 inches

Thready Qty Per Inch (tpi):

20 and 18

Thread Size:

0.812 inches and 1.125 inches

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Gold single mating end all contact groupings

Terminal Type:

Crimp single mating end all contact groupings

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416 federal specification single treatment response

Included Contact Quantity:

8 single mating end 2nd contact grouping

Bushing Accommodation Hole Shape:

Round w/flat

Included Contact Type:

Round pin single mating end all contact groupings

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.012 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef

Specification Data:

96906-ms27468 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-38999 spec.