NSN 5935-01-160-8644

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-160-8644 **Body Style:** Straight type **Overall Length:** 3.220 inches **Overall Width:** 0.440 inches **Unthreaded Mounting Hole Diameter:** 0.144 inches **Distance Between Mounting Facility Centers:** 2.812 inches **Mating End Quantity: Contact Position Arrangement Style:** 17 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 725.0 single mating end single contact grouping **Polarization Method:** Mating end Shell Type: Solid **Connector Locking Method:** Friction **End Application:** 6605lljb28946 **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Terminal Type:** Turret single mating end single contact grouping **Shell Material:** Aluminum **Shell Surface Treatment:**

Cadmium and iridium

NSN 5935-01-160-8644

Electrical Receptacle Connector - Page 2 of 2



Shell Material Specification:

Qq-a-591 federal specification single material response

Insert Material Specification:

Mil-m-14, ty mdg military specification single material response single mating end

Included Contact Quantity:

17 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.017 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.